



**Conveyor Frame:**

36" Deep Lattice Frame

**Idlers:**

- All standard idlers are CEMA B – 5" diameter
- 35 degree troughing idlers on 4' spacing
  - 20 degree idlers at feed point close spacing
  - Flat steel return idlers on 10' spacing

**Undercarriage:**

Manual telescoping pin lock  
 Axle – single axle with dual 11:00 – 22.5 tires on swivel wheel boxes

**Receiving Trough:**

5' 6" long with adjustable rubber flashing

**Belt Drive:**

- Head end drive
- 250 TPH capacity (100 pcf material)
- Class I TA3203 Dodge shaft mount reducer w/backstop
- 15 Hp - 3/60/460 TEFC electric motor
- V-belt, motor mounts and guards
- 16" dia., 3/8" grooved head pulley
- 14" dia. steel wing tail pulley
- 24" Screw take-up

**NOTE:**

Drawing is shown for informational purposes only, and may not necessarily represent the configurable options selected or available on the equipment. Specifications are subject to change without notice.

**Belt:**

2 ply 220 PIW, 1/8" x 1/16" covers with mechanical fasteners

**Belt Cleaner (Optional):**

Martin belt cleaner on head pulley of conveyor

**Paint:**

One coat of primer, finish coat of Beige acrylic

**Physical / Operating Characteristics:**

Overall Length ..... 125'-0" [38.1m]  
 Travel Length; king pin to tail ..... 64'-1" [19.5m]  
 Travel Height ..... 13'-7" [4.1m]  
 Travel Width ..... 11'-11" [3.6m]  
 Feed Height ..... 5'-4" [1.6m]  
 Maximum Discharge Height ..... 41'-8" [12.7m]  
 Minimum Discharge Height ..... 17'-1" [5.2m]

**Stockpile Capacities****(100 pcf material, 37.5° Angle of Repose):**

Conical Pile ..... 5,975 ton / 4,426 yd<sup>3</sup>  
 1° Pile Segment ..... 223 ton / 165 yd<sup>3</sup>  
 90° Pile ..... 26,060 ton / 19,304 yd<sup>3</sup>  
 180° Pile ..... 46,145 ton / 34,182 yd<sup>3</sup>  
 270° Pile ..... 66,230 ton / 49,059 yd<sup>3</sup>

**Options:**

Radial Hopper  
 Rock Box Hopper  
 Oversized Rock Box Hopper  
 AR Liners  
 Anchor Pivot  
 Undercarriage Lift Cylinder  
 7.5 Hp electric / hydraulic power pack  
 Power Travel – 2 Hp electric  
 Second Power Travel – 2 Hp electric  
 Pintle hitch  
 CEMA C Idlers  
 Impact Idlers (3)  
 Rubber disc return idlers  
 3 Ply, 330 PIW Belt  
 Vulcanized belt splice  
 Manual Top Folds (Head and Tail)\*  
 Hydraulic Top Folds (Head and Tail)  
 Hydraulic Axle Raise  
 Gullwing Axle  
 Planetary Drive for Gull Wing Axle  
 Landing Gear  
 Walking Beam Axle\*  
 King Pin\*  
 Travel Lights\*  
 Air Brakes\*

\*Recommended for Highway Portability



700 W. 21<sup>ST</sup> Street – P.O. Box 20  
 Yankton, South Dakota 57078  
 Phone: (605) 665-8771  
 FAX: (605) 665-8858  
[mail@kpijci.com](mailto:mail@kpijci.com)  
[www.kpijci.com](http://www.kpijci.com)

**NOTE: Specifications are subject to change without notice.**

Because KPI-JCI may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by KPI-JCI may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of KPI-JCI are subject to the provisions of its standard warranty. KPI-JCI does not warrant or represent that its product meet and federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the areas and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.