

FOLD 'N GO®

Self Contained Track Plant | Superior Toughness | Unmatched Screen Capacity

TRACK SCREENING PLANT



AGGREGATE AND MINING GROUP

All FAST TRAX high frequency screening plants feature the ultimate in screen production and efficiency. All FT track screening plants are designed for operation with track crushers in tight spots and comes with a double deck PEP Vari-Vibe® high frequency screen for a wide range of applications from crushed stone to RAP. As with all track screening plants offered by Astec Mobile Screens, the FT2618V Fold 'n Go offers totally self contained diesel power with standard wireless remote for plant movement. This track screening plant provides the highest screen capacity in the market for material separation ranging from 1" to 30M.

FT2618V FOLD 'N GO

1" to 30M

Highest screen capacity in the market in this size ranae.

125 HP

Tier III John Deere water cooled diesel engine to power all plant functions.

6'X18'

PEP Vari-Vibe® 2618V double deck high frequency screen.

Up to 350 TPH

Screening plant can process up to 350 TPH or more of feed material.

PERFORMANCE

PEP Vari-Vibe® 2618V This modified double deck high frequency screen: $6' \times 18'$ top deck and $6' \times 18'$

bottom deck for improved screen production.

Dust Cover

SAFETY

The vinyl dust cover provides dust control and cleaner air in the work area.

EASE-OF-USE

El Fast Setup


Quick setup times give producers more time to produce material.

Central Grease Points


Makes routine services easy.


DURABILITY


Stealth Tappet Design Redesign of this component makes the vibrators more durable.













STEALTH TAPPETS

Redesigned variable speed hydraulic vibrator tappets produce less sticking of material and better wear. Fourteen tappets are mounted below the screens for directly induced vibrating action.



HIGH FREQUENCY SCREEN

A double deck PEP Vari-Vibe® high frequency screen with hydraulic screen angle adjustment and rotary screen tensioning system can meet different aggregate application demands with ease.



SUPERIOR FINES REMOVAL

The PEP screen is unmatched in the industry for fines removal, especially in the 1/2" minus range in a wide range of applications, from crushed stone to RAP.

www.kpijci.com

PART OF THE FAST TRAX FAMILY OF **EQUIPMENT.**

Designed to run with the KPI-JCI family of tracked impactors to produce high capacities of saleable products.

SERVICE MADE EASY

Because we're dedicated to keeping you up and running, we've provided two resources for quality O.E.M. parts and 24/7 service. Astec Mobile Screens and KPI-JCI parts and service are available from you local dealer and/or representative.

Find the dealer or representative nearest you at www.kpijci.com.

Because Astec Mobile Screens may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by Astec Mobile Screens may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of Astec Mobile Screens are subject to the provisions of its standard warranty. Astec Mobile Screens does not warrant or represent that its products meet any federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHAGATOR, covering safety pollution, electrical, wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the area and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required, additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.