



# SLIDE-PAC™ AND SLIDE-STAC™ CONVEYORS

60' / 70' / 80'

- Specially designed field truss conveyors stack one on top of the other for transport, **saving you on shipping costs.**
- A portable transfer conveyor designed for **swift, reliable and safe** setup for operation or transportation.
- Engineered truss supports head end rollers for an **effortless glide** to and from stacked mode.
- Only **one operator** for setup or teardown.

# SPECIFICATIONS AND OPTIONS

## GENERAL SPECS

Tons Per Hour (TPH): **Up to 1,200**

Belt Widths (inches): **Up to 42**

Belt Speed (FPM): **350**

OPERATING DIMENSIONS	SLIDE-PAC CONVEYORS			SLIDE-STAC CONVEYORS	
	60'	70'	80'	60'	70'
Conveyor Length (m)	60'-0" (18.3)	70'-0" (21.3)	80'-0" (24.4)	60'-0" (18.3)	70'-0" (21.3)
Conveyor Ground Length (m)	58'-9" (18.0) to 59'-7" (18.2)	68'-10" (21.8) to 69'-7" (21.2)	79'-1" (24.1) to 79'-7" (24.3)	59'-8" (18.2)	66'-1" (20.1)
Raised Height to Center of Pulley (m)	Varies	Varies	Varies	Varies	Varies
Lowered Height to Center of Pulley (m)	Varies	Varies	Varies	Varies	Varies
TRAVEL DIMENSIONS					
Travel Length (m)	59'-8" (18.2)	73'-4" (22.3)	79'-8" (24.2)	59'-0" (18.0)	69'-0" (21.0)
Travel Height (m)	13'-6" (4.1)	13'-6" (4.1)	13'-6" (4.1)	13'-2" (4.0)	13'-5" (4.0)
Travel Width (m)	10'-1" (3.1)	9'-11" (3.0)	9'-11" (3.0)	11'-0" (3.3)	12'-0" (3.6)
Kingpin to Axle (m)	44'-9" (13.6)	54'-9" (16.6)	64'-9" (20.0)	37'-1" (11.3)	49'-2" (15.0)
Weight at Axle (kg)	19,000 (8,618)	21,000 (9,525)	22,000 (9,979)	24,700 (11,203)	28,300 (12,836)
Weight at Kingpin (kg)	10,000 (4,535)	12,700 (5,760)	13,900 (6,304)	6,800 (3,084)	11,200 (5,080)



**SLIDE-STAC UNDERCARRIAGE**



**ROLL-ON/ ROLL-OFF CAPABILITY**



**SLIDE-PAC OPERATION**

- EXTERRA® PRIMARY BELT CLEANER
- EXTERRA® SFL DUAL BELT CLEANER
- URATHON® RETURN ROLL
- LIGHTING PACKAGE

- ADJUSTABLE HEIGHT DISCHARGE
- RADIAL HOPPER
- MOXIE® ROLLS
- IMPACT IDLERS

- BELT COVERS
- AUTO GREASERS

See video at [bit.ly/slide-pac](https://bit.ly/slide-pac)