



Conveyor Frame:

24" Deep Lattice Frame

Idlers:

- All standard idlers are CEMA B – 5" diameter
- 35 degree troughing idlers on 4' spacing
 - 20 degree idlers at feed point close spacing
 - flat steel return idlers on 10' spacing

Undercarriage:

Manual telescoping pin lock
 Axle – single axle with single 11:00 – 22.5 tires on swivel wheel boxes

Receiving Trough:

5' 6" long with adjustable rubber flashing

Belt Drive:

- Head end drive
- 250 TPH maximum capacity (100 pcf material)
- Class I TA2115 Dodge shaft mount reducer w/backstop
- 10 Hp - 3/60/230-460 TEFC electric motor
- V-belt, motor mounts and guards
- 16" dia., 3/8" grooved head pulley
- 14" dia. steel wing tail pulley
- 12" Screw take-up

NOTE:

Drawing is shown for informational purposes only, and may not necessarily represent the configurable options selected or available on the equipment. Specifications are subject to change without notice.

Belt:

2 ply 220 PIW, 1/8" x 1/16" covers with mechanical fasteners

Belt Cleaner (Optional):

Martin belt cleaner on head pulley of conveyor

Paint:

One coat of primer, finish coat of Beige acrylic

Physical / Operating Characteristics:

Overall Length 70' [21.3m]
 Travel Length; king pin to tail 69'-2" [21.1m]
 Travel Height 13'-1" [4.0m]
 Travel Width 11'-11" [3.6m]
 Feed Height 5'2" [1.6m]
 Maximum Discharge Height 23'-7" [7.2m]
 Minimum Discharge Height 13'-10" [4.2m]
 Travel Weight (king pin) 3,000 lbs
 Travel Weight (axle) 11,500 lbs

Stockpile Capacities

(100 pcf material, 37.5° Angle of Repose):

Conical Pile 1,176 ton / 871 yd³
 1° Pile Segment 42 ton / 31 yd³
 90° Pile 4,981 ton / 3,690 yd³
 180° Pile 8,787 ton / 6,509 yd³
 270° Pile 12,592 ton / 9,327 yd³

Options:

Radial Hopper
 Rock Box Hopper
 Oversized Rock Box Hopper
 Hydraulic Drive
 AR Liners
 Anchor Pivot
 Undercarriage Lift Cylinder
 7.5 Hp electric/hydraulic power pack
 Power Travel
 Pintle hitch
 Impact Idlers (3)
 Rubber disc return idlers
 CEMA C idlers
 3 ply, 330 PIW belting
 Vulcanized belt splice
 Manual Top Fold (Head End Only)
 Hydraulic Top Fold (Head End Only)
 King Pin*
 Dual Tires*
 Travel Lights*
 Air Brakes*
 *Recommended for Highway Portability



700 W. 21st Street – P.O. Box 20
 Yankton, South Dakota 57078
 Phone: (605) 665-8771
 FAX: (605) 665-8858
mail@kpijci.com
www.kpijci.com

NOTE: Specifications are subject to change without notice.

Because KPI-JCI may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by KPI-JCI may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of KPI-JCI are subject to the provisions of its standard warranty. KPI-JCI does not warrant or represent that its product meet and federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the areas and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.