



Conveyor Frame:

24" Deep Lattice Frame

Idlers:

All standard idlers are CEMA B – 5" diameter

- 35 degree troughing idlers on 4' spacing
- 20 degree idlers at feed point close spacing
- Flat steel return idlers on 10' spacing

Undercarriage:

Manual telescoping pin lock

Axle – single axle with single 11:00 – 22.5 tires on swivel wheel boxes

Receiving Trough:

5' 6" long with adjustable rubber flashing

NOTE:

Drawing is shown for informational purposes only, and may not necessarily represent the configurable options selected or available on the equipment. Specifications are subject to change without notice.

Belt Drive:

- Head end drive
- 750 TPH capacity (100 pcf material)
- Class I TA3203 Dodge shaft mount reducer w/backstop
- 15 Hp - 3/60/230-460 TEFC electric motor
- V-belt, motor mounts and guards
- 16" dia., 3/8" grooved head pulley
- 14" dia. steel wing tail pulley
- 12" Screw take-up

Belt:

2 ply 220 PIW, 1/8" x 1/16" covers with mechanical fasteners

Belt Cleaner (Optional):

Martin belt cleaner on head pulley of conveyor

Paint:

One coat of primer, finish coat of Beige acrylic

Physical / Operating Characteristics:

Overall Length	40' [12.2m]
Travel Length; king pin to tail	39'-4" [12.0m]
Travel Height	11'-4" [3.5m]
Travel Width	11'-11" [3.6m]
Feed Height	5'-4" [1.6m]
Maximum Discharge Height	14'-5" [4.4m]
Minimum Discharge Height	11'-5" [3.5m]
Travel Weight (king pin)	3,400 lbs
Travel Weight (axle)	9,000 lbs

Stockpile Capacities

(100 pcf material, 37.5° Angle of Repose):

Conical Pile	264 ton / 195 yd ³
1° Pile Segment	9 ton / 7 yd ³
90° Pile	1,067 ton / 790 yd ³
180° Pile	1,870 ton / 1,385 yd ³
270° Pile	2,673 ton / 1,980 yd ³

Options:

Radial Hopper
 Rock Box Hopper
 Oversized Rock Box Hopper
 Hydraulic Drive
 Self-Contained Power
 AR Liners
 Anchor Pivot
 Undercarriage Lift Cylinder
 7.5 Hp electric/hydraulic power pack
 Power Travel
 Pintle hitch
 Impact Idlers (3)
 Rubber disc return idlers
 CEMA C idlers
 3 ply, 330 PIW belting
 Vulcanized belt splice
 King Pin*
 Dual Tires*
 Travel Lights*
 Air Brakes*
 *Recommended for Highway Portability



700 W. 21st Street – P.O. Box 20
 Yankton, South Dakota 57078
 Phone: (605) 665-8771
 FAX: (605) 665-8858
mail@kpijci.com
www.kpijci.com

NOTE: Specifications are subject to change without notice.

Because KPI-JCI may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by KPI-JCI may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of KPI-JCI are subject to the provisions of its standard warranty. KPI-JCI does not warrant or represent that its product meet and federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the areas and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.