



#### Primary Hopper Belt Feeder:

The primary hopper has a 9 cubic yard capacity with a top opening of 12' x 6'-0". The hopper is constructed of 1/4" thick A-36 steel.

The primary belt feeder is positioned underneath the primary feed hopper. The belt feeder is powered with a 7.5 hp variable speed electric drive. The feeder has a belt-width of 30" and is 10'-9" long.

#### Feed Conveyor:

The feed conveyor transfers material from the feed hoppers to the pugmill mixing box. It has a heavy duty channel-type frame, and is powered with a 7.5 hp electric head end drive. The conveyor is 29'-0" long and has a belt width of 30".

#### Pugmill:

The twin shaft pugmill consists of an enclosed 4' x 6' mixing box with AR steel liners. Enclosed in the mixing box are two heavy-duty 6" XH counter rotating shafts. These shafts include 40 double tip Ni-hard paddles in an overlapping spiral arrangement. Paddle tips have an adjustable wall clearance range of 3/4" to 2".

Power is transferred to the rotating shafts from a 60 hp electric motor through a v-belt drive. The reducer drives a single shaft which in turn powers the other shaft through a set of timing gears that rotate in an oil bath.

It includes an adjustable dam gate, a receiving hood with spray bar, inspection doors, and a drop out bottom to provide access for easy clean out.

#### Chassis:

The pugmill plant's portable chassis consists of a heavy duty channel-style frame with a gooseneck and kingpin located at the feed end of the plant. The chassis utilizes a walking beam-type tandem axle with dual 11.0 x 22.5 tires (8 total) located at the discharge end. The plant includes manual landing gear.

### Secondary Hopper: (Optional)

The optional secondary hopper has a 6.5 cubic yard capacity with a 12' x 6'-0" top opening. The hopper is constructed of 1/4" thick A-36 steel.

The secondary belt feeder is positioned underneath the secondary feed hopper. The belt feeder is powered with a 3 hp variable speed electric drive. The feeder has a belt-width of 30" and is 10'-9" long.

### Water System: (Optional)

The water system includes a 150 gpm pump with 3 hp variable speed drive, flowmeter, and a valve. The system can be configured to be adjusted manually or automatically from the control system.

### Asphalt System: (Optional)

The asphalt system includes a 90 gpm pump (powered by a 10 hp motor), a flowmeter, and a valve. The system can be configured per customer request to be adjusted manually or to be automatically proportioned.

### Walkway:

The 24" wide walkway gives the operator access to the pugmill mixing chamber. It consists of an operator's platform and a stairway with handrail to provide access to the platform from the ground.

### Automatic Proportioning:

Automatic Proportioning is a feature that utilizes feedback from a belt scale to automatically adjust the amount of additives (e.g. water, asphalt, fly ash) that will be combined with varying amounts of material being fed to the pugmill mixing box.

### Controls:

Controls for the pugmill plant are located on a ground accessible panel mounted to the side of the plant. Operators have start/stop capability for the plant as well as the ability to vary both the speed of the belt feeder and the rate at which any additives will be blended into the feed material.

### Physical / Operating Characteristics:

Overall Length .....	51'-3"[15.6]m
Travel Length; kingpin to tail: .....	48'-7"[14.8]m
Travel Height .....	13'-6"[4.1]m
Travel Width .....	10'-9"[3.3]m
Feed Height.....	13'-6"[4.1]m
Discharge Height.....	7'-9"[2.4]m
Travel Weight (kingpin) .....	10,400 lbs
Travel Weight (axle) .....	26,700 lbs

### Mixing Capacities (100 pcf material):

Dry Material Throughput .....	up to 300 TPH
Water System (Optional).....	150 GPM
Asphalt System (Optional) .....	90 GPM

### Options:

- Belt Scale
- Dry Solids Flowmeter
- Diesel Genset (95 KW)
- Hydraulic Dribble Gate with Power Pack
- Water System
- Asphalt System
- Discharge Hood



700 W. 21<sup>st</sup> Street – P.O. Box 20  
Yankton, South Dakota 57078  
Phone: (605) 665-8771  
FAX: (605) 665-8858  
[mail@kpijci.com](mailto:mail@kpijci.com)  
[www.kpijci.com](http://www.kpijci.com)

**NOTE: Specifications are subject to change without notice.**

Because KPI-JCI may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by KPI-JCI may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of KPI-JCI are subject to the provisions of its standard warranty. KPI-JCI does not warrant or represent that its product meet and federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the areas and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.